



PRODUCT SPECIFICATIONS

Material:	100% Eucalyptus (Eucalyptus regnans)
Resin:	Proprietary Binder (non-toxic & water resistant)
Finish:	Multi-layer UV cured Acrylic System
Sizes:	9/16" x 4-3/4" x 72"
Fire Rating:	Critical Radiant Flux: Average of .53 - .59 W/sq cm when tested in accordance with ASTM E 648. Class 1
Flame Smoke Index:	Smoke Density (Flaming): Dmc 241 in accordance with ASTM E662-09, NFPA 258 : Avg. Specific Optical Density at 4.0 Minutes, 8. Smoke Density (Non-Flaming): Dmc 417 in accordance with ASTM E662-09, NFPA 258 : Avg. Specific Optical Density at 4.0 Minutes, 3.
Hardness:	Average range of 2790 to 3439 lbf, Janka Ball hardness test; ASTM D 1037.
Dimensional Stability:	At 90 percent relative humidity; ASTM D 1037, Section 24. a. Length: 0.04 percent change. b. Width: 0.20 percent change.
Coefficient of Friction:	Average of 0.44 for static friction between flooring and prime grade shoe leather sole when tested in accordance with ASTM D 2394.
Formaldehyde Emissions:	Less than 0.007 parts per million, tested in accordance with ASTM E 1333.

INSTALLATION

See Green Choice Installation Instructions for full detail.

Methods

Glued down to a wood or concrete subfloor.

For a glue down application Green Choice recommends use of a premium, 100% urethane-based, wood flooring adhesive (Bostik's Best Adhesive, Bostik's TKO or similar.)

Floating over suitable subfloor, with recommended vapor barrier and/or acoustic underlayment.

Moisture Areas

Special precautions should be taken below grade. An adhesive with vapor barrier qualities is recommended for these installation environments. For floating installation, a vapor barrier is recommended.

High Traffic Areas

A top coat sealer can be applied, and is recommended for areas with higher traffic volumes, and areas which have a higher probability of experiencing moisture related spills. Please consult with a certified floor refinisher to determine the best product for your application.

WARRANTY

Lifetime Structural Warranty

Refer to Green Choice Flooring International Warranty for more details.

25/5 year Pre-Finish Warranty

The Manufacturer warrants that the aluminum oxide finish on flooring planks will not wear through or separate for 25 years in residential applications and 5 years in commercial applications. Refer to Green Choice Flooring International Warranty for more details.

LEED® INFO

LEED Submittals

Credit MR 6, Rapidly Renewable Materials

Credit IEQ 4.1, Low-Emitting Materials, Adhesives & Sealants

Credit IEQ 4.4, No added formaldehyde

MEMBER OF:



National Wood Flooring Association



WORLD FLOOR COVERING ASSOCIATION

